

Introducing the newest member of our Intercon 1 Camera Link[®] Family



Infini Flex[™] 
Camera Link[®]
CABLE ASSEMBLIES

Featuring

GORE[™] Camera Link[®] High Flex Flat Cable

- Designed specifically for cable carrier applications
- High performance flex life while maintaining signal integrity
- Worry free performance
- Non particulating cable jacket for clean rooms
- Flexing bend radius as small as 50mm



Intercon 1

A Division of Nortech Systems

Camera Link[®] • Mini Camera Link[®] • Power Over Camera Link[®]

800-237-9576 • intercon@nortechsys.com • www.intercon-1.com



Infini Flex™ Camera Link®

CABLE ASSEMBLIES

featuring GORE™ Camera Link® High Flex Flat Cable

Reliable Flex Life Performance

Infini Flex™ Camera Link® cable featuring GORE™ Camera Link® High Flex Flat Cable provide motion control and vision systems with reliable interconnects for high performance flex life and signal transmission. These assemblies should be used to avoid bit errors in moving Camera Link® systems. Infini Flex™ Camera Link® cable featuring GORE™ Camera Link® High Flex Flat Cable provide peace of mind when reliable system performance and equipment uptime are critical.

KEY FEATURES

- Cables can be customized for unique requirements
- Flat cable is non-particulating for clean room use
- Incorporates 26-position 3M MDR connectors
- Designed to surpass 10 million cycles
- Robust overmolding
- Unique quad construction

KEY BENEFITS

- Prevents lost data/data integrity problems
- Longer flex life
- Prevents system downtime
- Can be used for 50 mm bend radius

Ordering Information

Part Number	IF-CLCP-XX-P
XX equals the cable length in meters Example: IF-CLCP-10-P equals a 10 meter length	

Custom lengths and configurations are available



Intercon 1
A Division of Nortech Systems

800-237-9576
intercon@nortechsys.com
www.intercon-1.com